

Compact high vacuum unit, the ideal solution for removing dust and fumes



The compact E-PAK for multi-purpose use. is the ideal solution for the extraction of sanding and grinding dust and for welding fumes. Also suitable for cleaning of the workplace and the shop floor. The E-PAK is a powerful vacuumunit and can serve up to six extraction points, all in use at the same time. Typical areas of application can be found in welding shops, car body shops, construction industries, bakeries. industrial laundries etc.

Power control can be obtained by fitting automatic vacuum valves to the extraction points. The valves provide suction power when an operation starts. When the work stops and all the valves have closed again, the E-PAK unit will stop.

Automatic vacuum valves offer substantial energy savings and make a small unit manage the job otherwise requiring a large unit. Using automatic valves multiplies the number of workingpoints that can be served, by three to four times.

Low noise level is an obvious demand in today's workingenvironment. E-PAK is developed to fit into normally noise sensitive premises thanks to efficient silencers and acoustic enclosure. The enclosure is easily removed for service.

- · Easy to install
- Low noise level
- · Low running and maintenance costs
- · Low noise level

Product name	E-PAK 500
Noise level (dB(A))	67
Compressed air requirement	Dry and clean (Ø6 connection)
Installation	Indoor
Filter cleaning method	Reverse air pulse
Application	Dust, Granulate, Grit, Fumes, Swarf
Working pressure (kPa)	15
Max Airflow (m3/h)	860
Filter Area (m2)	3,4
No of phases	3
Filter type	Bag
Filter material	PTFE
Noise level (dB(A))	67
Capacity (max airflow m3/h)	
Max vaccum (kPa)	-25
Weight (kg)	333
Power (kW)	13



 ϵ

Granulate

ulate Grit

Fumes

Dust





Power Voltage (V)	Frequency (Hz)	Model
230	50	40051420
400	50	40051430
208	60	40051440
230	60	40051450
460	60	40051460
575	60	40051470
380	60	40051355



Accessory		Part No
	Replacement main filter for E-PAK DX with 16 antistatic filter socks.	40376777
	Silencer LT100 discharge	40139081
	Bend spiro BU 100mm 90dgr	40130820
	Grating spiro 100mm	40130220







^{*)} outlet diameter inner/outer (spiro)

^{**)} inlet outer diameter