

## Hose Reel 886 Stainless

Stainless steel hose reel when corrosive resistance is required ideal for food processing industries.



This stainless steel hose reel, made entirely of stainless steel, is designed specifically for the food processing industry. It is very easy to clean thanks to rounded edges and features an easy to dismantle hose outlet, an externally mounted swivel, and a minimum number of material joints.

- Unique design makes easy cleaning
- Up to 25 m (82 ft.) hose capacity
- Meets international hygienic requirement

Product name	Hose Reel 886 Stainless
Connection hose length (m)	Not included with reel. sold separatley
Delivered with hose	No
Colour	Stainless



# Hose Reel 886 Stainless

Image	Description	Type of hose	Media	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length	Note	Model
			Compressed air ,Water			12.5	10	28	25	NPT	32800386*
			Water high pressure			10	25	28	25		30801386
			Water			12.5	10	28	25		30800386
			Water			19	2	28	18		30800186
			Water			25	2	28	10		30802186
			Water/Steam			19	0,6 (Steam, 160 °C) 2,0 (Water)	28	18		30805286
			Water/Steam			25	0,6 (Steam, 160 °C) 2,0 (Water)	28	10		30805086
	Connection Hose (1m)	I	Water		12,5		10	1			30344854
	Distribution hose	G	Water high pressure		10		25			With galvanized steel fittings	30344852**
	Connection Hose (1m)	H	Water high pressure		10		25			With stainless steel fittings	30373669***
	Connection Hose (1m)	E	Water ,Food		12,5		2			With galvanized steel fittings	30373670**
	Connection Hose (1m)	E	Water ,Food		19		2			With galvanized steel fittings	30373674**
	Connection Hose (1m)	E	Water ,Food		25		2			With galvanized steel fittings	30373664**
	Connection Hose (1m)	F	Water ,Food		12,5		2			With stainless steel fittings	30373671***
	Installation material for pipe connection Dia 63 mm.	F	Water ,Food		19		2			With stainless steel fittings	30373675***

# Hose Reel 886 Stainless

Image	Description	Type of hose	Media	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length	Note	Model
	Connection Hose (1m)	F	Water ,Food		25		2			With stainless steel fittings	30373666***
	Connection Hose (1m)	N	Water		19		10				30377082
	Connection Hose (1m)	N	Water/Steam		25		0,6				30377081
	Distribution hose	G	Water high pressure	25		10	25			With galvanized steel fittings	30371900**
	Distribution hose	H	Water high pressure	25		10	25			With stainless steel fittings	30371953***
	Distribution hose	I	Water			12,5	10				30377078
	Distribution hose	E	Water ,Food	25		12,5	2			With galvanized steel fittings	30371898**
	Distribution hose	E	Water ,Food	18		19	2			With galvanized steel fittings	30371897**
	Connection Hose (1m)	E	Water ,Food	10		25	2			With galvanized steel fittings	30373663**
	Distribution hose	F	Water ,Food	25		12,5	2			With stainless steel fittings	30371951***
	Distribution hose	F	Water ,Food	18		19	2			With stainless steel fittings	30371950***
		F	Water ,Food	10		25	2			With stainless steel fittings	30373665***
	Distribution hose	N	Water/Steam			19	0,6				30377080
	Distribution hose	N	Water/Steam			25	0,6				30377079

\*NPT

\*\*With galvanized steel fittings















\*\*\*With stainless steel fittings

# Hose Reel 886 Stainless

<sup>1</sup> See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
I	Cover and inner tube in SBR based rubber. Single steel braid	-40 - 100	Female 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155	Female 60° cone, chrome plated. With rubber hose grip	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
H	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155	Female 60° cone, stainless steel. With rubber hose grip	Female 60° cone, stainless steel	Male 60° cone	Male 60° cone
E	Cover in NBR/PVC and inner tube in food grade quality NBR. Synthetic textile braid	-30 - 100	Male 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
F	Cover in NBR/PVC and inner tube in food grade quality NBR. Synthetic textile braid	-20 - 100	Male 60° cone, stainless steel	Female 60° cone, stainless steel	Male 60° cone	Male 60° cone
N	Cover in NBR/PVC and inner tube in food grade quality NBR. Synthetic textile braid. Max pressure: 0,6 MPa (Steam(164 °C)) and 2,0 MPa (Water)	-20 - 164	Male 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone

# Hose Reel 886 Stainless

Accessory		Part No
	Pivoting Wall bracket Stainless Steel	30373668
	Roller guide.	30341550
	Water gun in chromium plated brass	30400110
	Water gun in stainless steel	30400210
	Watergun EX	30400211
	High temperature water gun	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl. 1/2(m)-3/8(f) brass	30431510
	Swivl.coupl. 1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl. 1/2(m)-3/4(f) SS	30432010

# Hose Reel 886 Stainless

