

Versatile hose reel that can be mounted on wall or ceiling.



Medium-sized reel in robust open design. Thanks to the open design, the reels are very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling. Versatile and easily installed in industrial and workshop environments.

- Open design for easy cleaning and servicing
- · Unique stand design offers mounting flexibility

Product name	Hose Reel 893
Material recycling (% weight)	100
Connection hose length (m)	1
Colour	Black drum / Blue cover
Weight (kg)	14,5
Note	For suction hose

 ϵ



Type of hose ¹	Media	Delivered with hose	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Max hose length	Model
	Compressed air ,Water	No	10		12.5	1,5	10	30800793
	Compressed air ,Water	No	15		10	1,5	15	30800393
В	Compressed air ,Water	Yes	15	12.5	10	1,5		30800693
	Water high pressure	No	15		10	25	15	30801793
G	Water high pressure	Yes	15	10	10	25		30801893
J	Grease	Yes	15	6	6	35		30802693
I	Oil	Yes	10	12.5	12.5	7,5		30801693
В	Compressed air ,Water	Yes	10	12.5	12.5	1,5		30800893
	Oil	No	10		12.5	7,5	10	30801593
	Grease	No	15		6	35	15	30802593
		No	10		12.5		10	30804993*
E	Food	Yes	10	12.5	12.5	2		30801093

^{*}For suction hose

¹ See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
В	Cover in NBR/PVC and inner tube in NBR. Syntethic textile braid	-30 - 100	Male, chrome plated		Hose nipple + clip	Hose nipple 1/2" + clip
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155	Female 60° cone, chrome plated. With rubber hose grip	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
J	Cover and inner tube in syntetic, oil resistant rubber. Double steel braid	-40 - 100	Female 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
I	Cover and inner tube in SBR based rubber. Single steel braid	-40 - 100	Female 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
E	Cover in NBR/PVC and inner tube in food grade quality NBR. Syntethic textile braid	-30 - 100	Male 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone



	Accessory	Part No
	Roller guide.	30341550
	Pivoting bracket.	30372407
	Water gun in chromium plated brass	30400110
1	Water gun in stainless steel	30400210
	Watergun EX	30400211
	High temperature water gun	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl.1/2(m)-3/4(f) SS	30432010



